

MACTEXTURE ROLL-ON FINISHES

Acrylic-based textured finishes formulated for roller application.

Description

MAC manufactures a range of premium quality interior/exterior acrylic textured finishes, formulated specifically for roller application. Available in a range of textured effects, MAC roller applied coatings can be tinted to an almost infinite range of fashionable colours.

Composition

Mactexture is manufactured using only the highest quality raw materials available. These include marble aggregates, selected fillers, mould growth inhibitors and premium grade acrylic polymer emulsions.

Product Range

- > Rustic (low/medium stipple effect)
- > Tuscan (heavy stipple effect)



Colour Range

Mactexture is supplied in its natural form as an off-white paste but can be tinted to almost any colour from all popular ranges, from deep tones to pastels.

Prior to Application - A Note On alkalinity

Application of acrylic finishes over fresh cement based renders can lead to coating degradation caused as a result of high pH (alkalinity). Acrylic finishes should not be applied over renders until the pH has fallen to 9 or less. This can take around 5 days or even longer. Application on renders with a pH greater than this may result in lime burn and other problems. Render alkalinity can be checked by dampening the wall with distilled water and applying commonly available pH indicator paper.

Application & Finishing

Prior to commencement of work, ensure a test panel has been completed and approved for both colour, texture, and surface finish. Prior to the coating application, ensure that the substrate is clean and free of any impurities that may compromise adhesion. Loose and flakey material must first be removed with a pressure cleaner.

Fill a paint roller tray and thoroughly wet-out the selected texture roller cover. Generously apply Mactexture Rustic or Tuscan to the wall with a textured roller cover. Spread the fresh material over the wall taking care to coat evenly. Apply in up and down motion but always perform the finishing stroke in the same direction to produce a uniform appearance. Work quickly and always maintain a 'wet-edge'. It is important to not thin the material or over spread the coating. Cutting in with a brush must be carried out simultaneously and over-rolled to reproduce the correct textured effect. To help with work-flow on larger walls, ensure scaffold is erected and loaded with sufficient product. This will eliminate any stop/start activity which may result in unsatisfactory results.

Tips on Application

It is imperative to maintain a 'wet-edge' during application of Mactexture coatings. All faces should be completed in a single session avoiding dry-joins at all costs. Where possible, avoid working in direct sunlight and excessively hot or windy conditions. Mactexture should only be applied in temperatures ranging between 10 and 26 C. Application in hot or windy conditions will accelerate drying, making finishing difficult. Do not apply material if temperature is to fall below 10 C during the drying process. This may result in inadequate film formation in the finished coating.

Newly coated areas should be protected from moisture for a period of 24 hours minimum from the time of application. To ensure colour uniformity across the entire project, always order sufficient material to coat the job in one batch. It is also advisable to cross-mix drums during the application process.

Coating Details

PRODUCT NAME	COATING THICKNESS	APPEARANCE	APPROX. COVERAGE
<i>Rustic</i>	<i>0.6 mm</i>	<i>Fine/medium stipple</i>	<i>30 m2 / 15 litre</i>
<i>Tuscan</i>	<i>1.2 mm</i>	<i>Heavy stipple</i>	<i>16 m2 / 15 litre</i>

Coverage

Mactexture will cover between 16-30 square metres per 15 litre pail depending on grade. Refer to table for details.

Supply & Packaging

Mactexture is supplied pre-tinted to the selected colour in 5 and 15 litre plastic pails. Mactexture can also be supplied in pallet lots, tinted or natural containing 48 x 15 litre pails.

Clean Up

Mactexture is an acrylic based product. All tools and equipment should be washed in clean water immediately following use.

Safety

Mactexture is non-toxic prolonged exposure may cause skin irritation. MAC strongly recommend the use of skin and eye protection during application. Refer to MSDS for details. Always ensure scaffolding used during application conforms to local government requirements.

IMPORTANT NOTE:

Melbourne Acrylic Coatings Victoria Pty Ltd, its staff and distributors will not accept responsibility for any failure caused as a result of factors beyond our control including but not limited to onsite handling, preparation or application of this product. Application of this product should only be performed by qualified trades people trained in the use of this type of product. Information supplied in this publication is based on our testing and experience and is given in good faith. Suitability of this product should be independently determined prior to use. Warranty is limited to the replacement of any materials proven to be faulty. MAC will not warrant job defects caused as a result of but not limited to, structural/substrate movement or entrapped moisture.

